

1 Motivation and Goals

Currently: Nation Ford Chemical processes a wastewater stream with 3,300 mg/L of TDS

Future: Implement process that will produce additional stream with 23,083.3 mg/L of TDS

New Regulation POTW has proposed a new TDS limit of 1,500 mg/L


Goals

- Lower TDS of combined process stream below 1500 mg/L using reverse osmosis
- Create an economical separation process
- Minimize safety hazards by implementing control and safety equipment

2 Technical Background

Reverse Osmosis: pressurized feed ran across membrane configuration.

- Permeate has low concentration of contaminants
- Concentrate has high concentration of contaminants
- Operable range of pressures to satisfy design needs
- Range and bounds found through sensitivity analysis




Reverse Osmosis Diagram

Reverse Osmosis, <https://www.sciencefacts.net/reverse-osmosis.html>

3 Design

Process Flow Diagram



Equipment Selection


Equipment Name	Type	MOC
Mixer	Mixing Tank (built in agitator)	SS 316
Pumps	Centrifugal	SS 316
Heat Exchanger	Shell and Tube	Shell: CS // Tube: SS 316
Valves	Pressure Relief // Globe	SS 316
Index Tank	Welded Equalization Tank	SS 316
RO System	FilmTec™ Eco Pro-400 Element	Membrane: Polymer // Housing: SS 316
Piping	Stainless Steel	SS 316

Stream Table

Stream Number	10	10A	10B	14A	18	20A	21
Temperature (°C)	21.11	21.11	21.11	21.11	21.11	21.11	21.11
Pressure (psi)	295.00	287.50	295.00	165.00	19.00	19.00	14.70
Flow Rate (gal/min)	8.63	2.07	8.63	6.93	3.31	6.62	0.33
Component Flow Rate (kmol/h)							
Salt 1	0.19	0.04	0.18	0.17	0.01	0.03	0.0008
Salt 2	0.21	0.07	0.31	0.29	0.02	0.05	0.0013
Water	53.78	25.80	107.57	86.22	41.63	83.26	4.15
TDS Mole Percentage	0.73%	0.45%	0.45%	0.21%	0.09%	0.09%	0.05%


4 Economic Analysis

Capital Cost



Final Capital Cost: ~\$756,000

Operating Cost



Total Operating Cost: ~\$2,850,000

Return on Investment

1st Year ROI: ~ -26.3% **3-Year ROI: ~ -32.5%**

5 Hazards and Operability

HAZOP Guidewords- More, Less, No

HAZOP Recommendations

- Use a composition analyzer to determine the effectiveness of the RO separation
- Apply secondary containment such as a dike in the event of loss of containment from an overflow in the index or mixing tanks
- Have regular functionality checks of process equipment
- Add insulation to process piping

6 Conclusions

The Process is Not Suited for Commercialization

- From a technology standpoint, the project is feasible. RO is widely used in industry.
- To produce half of the volumetric input, there would need to be 27 passes
- The maintenance and energy consumption of so many passes is so expensive that the final ROI will -26.35% after 1 year of operation

Acknowledgments and References

We would like to thank our mentor, Dr. Phillip McCarter, for his time and guidance throughout this project, as well as Dr. Bullard and Dr. Cooper for their teaching expertise.

