

Motivation and Goals


Reshore production of a subcooling organic intermediate back to the US

- Design a continuous solidification process
- Create an economically viable design
- Perform a HAZOP safety analysis

Solid allows for better storage and transport
Opportunity for Nation Ford to be one of the first to enter the domestic market

Technical Background


- Organic intermediate is subcooler
- Prilling decided as the best option → transforms melts into spherical prills
- Small energy consumption, simple process, scalability potential, and product uniformity



<https://www.shutterstock.com/search/prilling-tower>

Process Design

Process Flow Diagram



Equipment Summary


Equipment Name	Type	Important Specifications	MOC
Pump	Centrifugal	Shaft Power: 0.94 kW Efficiency: 0.68	CS
Heat Exchanger	Shell and Tube	Heat transfer area: 8 ft ² Cooling Water Temp: 10°C or 32°C	CS
Tower	Prilling Tower	Height: 76 ft Diameter: 9.66 ft	CS
Fan	Centrifugal	Diameter: 5 ft Width: 2.6 ft	CS
Dust Collector	Baghouse	Filtration Area: 1242 ft ² Number of bags: 156	CS
Valves	Pressure Relief/Safety	Relief Valves: Liquid Streams Safety Valves: Gas Streams	CS

Stream Table

Stream	1	2	3	4	8	10
Temperature (°C)	95	95.135	90	65	50	50.001
Pressure (psi)	14.696	44.088	44.088	14.696	14.696	13.971
Flowrate (gal/min)	50	50.004	49.848	49.84	164474	0.0083
Product Phase	Liquid	Liquid	Liquid	Solid Prills	Air/Solid Dust	Solid Dust
MOC	CS	CS	CS	CS	CS	CS
Pipe Diameter (in)	3	3	3	3	48	0.125
Schedule	40	40	40	40	40	40

Economic Analysis

Capital Cost of Major Equipment



Net Present Value (MM)	2.97
Disc. Cash Flow ROR (%)	25.31
Disc. Payback Period (years)	2.4
Cumulative Cash Position (MM)	17.03

Total Module Cost:

\$2.1 million

Safety and Hazards

- Components: pump, heat exchanger, prilling tower, centrifugal fan, baghouse collector
- Parameters of interest: flow rate, temperature, pressure, and prill size
- Deviations: more, less, no
- Major concerns: overpressurization, clogging, solidification of organic intermediate in the pipes, prill inconsistency, explosion
- Actions: pressure relief valves, indicators, controllers, heat traced insulated pipes

Conclusions and Recommendations

- Process shown to be economically viable as a long-term investment;
- Benefits of prilling can increase market demand
- Further research needed on the physical properties organic intermediate

Acknowledgements

We want to thank our mentor, Dr. McCarter, as well as Dr. Bullard and Dr. Cooper for their help and guidance.

References

